

Solid State High Power Amplifier Systems

17-22GHz /51dB Gain/51dBm Psat/220V AC

Model: TLPA17G22G-51-51-BC

TLPA17G22G-51-51-BC is a solid state high power amplifier systems provides high output power and high gain across the 17 to 22 GHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Wide Band: 17-22 GHz
- Gain: 51dB Min
- Psat Output Power:51dBm Min
- Protection:Over TEM,over voltage, over current ,over VSWR protection
- 50 Ohm Matched Input / Output

电气特性 Electrical Characteristics:

参数 Parameter	代码 Symbol	Min	Typ	Max	单位 Units
频率范围 Frequency range	BW	17-22			GHz
功率增益 Power Gain	GP	51			dB
增益平坦度 Gain flatness	ΔGL			±4	dB
饱和输出功率 Output Psat	Psat	51			dBm
杂散 Spurious@Pout=53dBm	Spur			-60	dBc
谐波 Harmonics@Pout=53dBm	HAM			-20	dBc
输入驻波 Input VSWR	VSWRin			2.0	:1
交流电压 AC Voltage	Vac	220			V AC
功耗 Power Consumption	Pdiss			1200	Watts
阻抗 Impedance	I/O-IMP	50			Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/WR-51	
通信接口 Communication Connector	DB9/RJ-45	
液晶显示屏 Front Panel LCD Screen Display	7 inch LCD Screen Display	
尺寸 Size	19 Inch 4U	
重量 Weight	≤35	Kg

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



主要功能 Key Features:

参数 Parameter	特点 Advantages
控制功能 Control functions	1, Power setting On/Off
显示功能 Display functions	1,Output Power 2,Reflect Power 3,Fault Informations
内置保护功能 Protection functions	1,Over TEM 2,Over voltage 3,Over current protection 4,Over VSWR
监控和控制 Remote control	RS422/Ethernet
冷却系统 Cooling system	Built in Cooling system,forced air cooling

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+40	℃
存储温度 Non-operating Temperature*	-30		+50	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA17G22G-51-51-BC	Solid State High Power Amplifier Systems 17-22GHz,Gain:51dB,Psat:51 dBm,220V AC,Built in Fan Cooling	Rev.1.0